

Colour Laser Multifunctional Printer

i-SENSYS
MF8030Cn

you can



Share All-in-One high quality colour convenience.

Share full colour printing, copying and scanning with this compact unit. Network ready, easy to use and energy efficient, it puts professional colour quality within the reach of small businesses.

8 PPM COLOUR/ 12 PPM MONO PRINTING & COPYING
PAPER CAPACITY MAX.151-SHEET
QUICK FIRST-PRINT
UP TO 2400 X 600 DPI PRINT RESOLUTION
5-LINE LCD DISPLAY

Key features

- Compact colour laser All-in-One: print, copy and scan
- 8 ppm/cpm in colour, 12 ppm/cpm in mono
- Superior colour imaging technologies for crisp text and vibrant colours
- Up to 2400 x 600 dpi print resolution
- No waiting with Quick First-Print technologies
- User friendly 5-line LCD display
- Easy scan to network and to USB memory key
- 50-sheet ADF, 150-sheet cassette
- Energy efficient - only 3 watts in sleep mode
- Convenient All-in-One colour cartridges

What's in the Box

Main unit, Cartridge 716 starter C/M/Y/K, power cord, starter guide and warranty card - with user software and manual CDs.

Dimensions (W x D x H)

430 x 484 x 429 mm

Supported OS

Windows 2000/Server 2003/
Server 2008/XP/Vista
Mac OS X Version 10.4.9 - 10.5.x
(Web distribution only, network
scanning not supported)



PRINT



COPY




FAX



SCAN

Canon



- 1** Flatbed & 50-sheet ADF
- 2** 5-line LCD display
- 3** 150-sheet cassette
- 4** Cartridge 716
(4 colours available: Cyan, Magenta, Yellow and Black)

Machine type Available functions	Colour Laser All-In-One Print, Copy and Scan
PRINTER Print speed Printing method Print quality Print resolution Printer languages Print margins Toner saver mode	Up to 8 ppm colour (A4) Up to 12 ppm mono (A4) Colour laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement 600 x 600 dpi UFRII-LT 5 mm-top, bottom, left and right Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Multiple copy Reduction / Enlargement Other features	Up to 8 cpm colour (A4) Up to 12 cpm mono (A4) Colour Approx. 29 seconds or less Mono Approx. 23 seconds or less Up to 600 x 600 dpi Text/Photo/Map (Default), Text/Photo/Map (quality), Printed Image, Text Up to 99 copies 25-400% in 1% increments Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy
SEND FUNCTIONS Scan to USB memory key File formats	Yes PDF
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm
MEDIA HANDLING Scanner type Paper input (Standard) Paper output Media types Media sizes Media weights	Flatbed and Automatic Document Feeder (ADF) 150-sheet cassette 1-sheet manual feed slot 50-sheet ADF 125-sheet Plain paper, Recycled paper, Heavy Paper, Transparency, Coated Paper, Label, Index card, Envelope Cassette : A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5), Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm Manual feed slot: A4, A5, B5, Legal, Letter, Executive, Statement, Envelope (COM10, Monarch, DL, ISO-C5, ISO-B5), Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6 mm ADF: A4, A5, B5, Legal, Letter, Statement, Custom sizes (W x L): Max 215.9 mm x 355.6 mm; Min. 128 mm x 139.7 mm) Cassette: 60 to 163 g/m ² Manual feed slot: 60 to 220 g/m ² ADF: 50 to 105 g/m ²

INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX Windows 2000/ Server 2003/ Server 2008/ XP/ Vista Mac OS X version 10.4.9 - 10.5.x ^{1, 2} Presto! Page Manager, MF Toolbox, NetSpot Device Installer, Remote User Interface (RUI), Department ID Management
GENERAL FEATURES Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels	Max. 30,000 pages per month Approx. 30 seconds from power on 128MB (shared) 5 lines backlit LCD 430 mm x 484 mm x 429 mm 674 mm x 1229 mm x 801 mm Approx. 25 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V (±10%) 50/60Hz (±2Hz) Maximum: Approx. 900 W Standby: Approx. 16 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 0.62 kWh/week Sound Pressure ³ : Active: 63.4 dB(A) or less Standby: 50 dB(A) or less
CONSUMABLES Cartridges	Cartridge 716 Black (2,300 pages ⁴) Cartridge 716 Cyan (1,500 pages ⁴) Cartridge 716 Magenta (1,500 pages ⁴) Cartridge 716 Yellow (1,500 pages ⁴) ⁵
All specifications subject to change without notice	
¹ Web distribution only ² Network scanning not supported ³ Declared noise emission in accordance with ISO 9296 ⁴ Based on ISO/IEC 19758 ⁵ Printer ships with 800 pages CMYK (Cyan, Magenta, Yellow and Black) starter cartridges	

