

Embargo Date: 1st February 2010
Sales Start Date: March 2010
Target Market: Home



Key Features in Importance Order:

- 4800x1200dpi resolution and 2pl ink droplets for photolab-quality printing
- Photolab-quality 10x15cm borderless print in approximately 55 seconds
- ISO: ESAT print speed of 7.0/4.8 ipm mono/colour
- Pigment black ink for crisp, sharp text printing
- ChromaLife100+ system for long-lasting, beautiful photos
- Easy-WebPrint EX to easily clip, combine, edit and print from the web
- Easy-PhotoPrint EX to print your photos using Auto Photo Fix II
- Stylish and affordable entry-level model

Stylish and affordable home printing.

Ideal for anyone wanting an affordable home photo printer, the PIXMA iP2702 is stylish and easy to use and features 2pl ink droplets for photolab-quality printing.

The PIXMA iP2702 is part of the A4 PIXMA Photo Printer range.

The A4 PIXMA Photo Printer range consists of: PIXMA iP4700, PIXMA iP3600, **PIXMA iP2702**

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA iP2702	4103B026AA	4960999670768	£45 / €49

What's in the box: PIXMA iP2702 Printer, Power cord, Ink Cartridges PG-510 and CL-511, Multilingual set up guides, Setup software & User's manual CD including Easy-Photo Print EX, Warranty sheet

Consumables	Mercury Code	EAN Code	Recommended Retail Price
IJ cartridge PG-510	2970B001AA	4960999617015	£10.99 / €15.99
IJ cartridge CL-511	2972B001AA	4960999617039	£14.99 / €20.99
IJ cartridge PG-512 (option)	2969B001AA	4960999617008	£14.99 / €20.99
IJ cartridge CL-513 (option)	2971B001AA	4960999617022	£18.99 / €25.99

Note: Blister packs with and without security are available for each of the inks listed above

Technical Specifications

PRINTER FUNCTIONS	
Print Resolution	Up to 4800 ¹ x 1200 dpi
Print Engine	InkJet 4-ink with minimum 2 pl droplets and FINE Cartridge
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 55 seconds (Standard)
Mono Print Speed	ISO ESAT: Approx. 7.0 ipm
Colour Print Speed	ISO ESAT: Approx. 4.8 ipm
Ink Cartridge Configuration	FINE Cartridge - PG-510, CL-511 (Optional - PG-512, CL-513)
Black Ink Tank Life	Black: 220 pages (PG-510), 401 pages (PG-512) ² Black: 2955 photos* (PG-510), 7275 photos* (PG-512) ³ * Estimated supplemental yield
Colour Ink Tank Life	Colour: 244 pages (CL-511), 349 pages (CL-513) ² Colour: 83 photos (CL-511), 122 photos (CL-513) ³
Media Type	Plain Paper, High Resolution Paper (HR-101N), Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), Photo Stickers (PS-101), T Shirt Transfers (TR-301)
Media Input	Sheet Feeder: Max. 100 sheets
Media Size	Sheet Feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm
Media Weight	Sheet Feeder: 64 to 105 g/m ² and supported Canon special media up to 300 g/m ²
Two Sided Printing	Available by manual operation using plain paper (Windows only)
Borderless Printing	Yes (A4, Ltr, 20 x 25cm, 13 x 18cm, 10 x 15cm sizes)
INTERFACE AND SOFTWARE	
Interface Type - PC Supported	Hi-Speed USB (B port)
Operating System	Windows 7, Windows Vista, Vista SP1 / Windows XP SP2, SP3 / Windows 2000 Professional SP4 Mac OS X v.10.4 - v.10.6
Software Included	Easy-PhotoPrint EX, Easy-WebPrint EX downloader, Canon Utilities MyPrinter, Canon Utilities Solutions Menu

GENERAL FEATURES	
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Standby: Approx. 0.7W Off: Approx. 0.4W Printing: 11W ⁴
Temperature Range	Operating environment: 5° - 35°C
Humidity	Operating humidity: 10 - 90%RH (no condensation)
Acoustic Noise Levels	Approx. 47.0dB (A) When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings
Dimensions (W x D x H)	445 x 249 x 130mm
Weight	Approx. 3.4kg

All specifications subject to change without notice.

Borderless 10x15cm photo lab quality print speed based on Standard driver setting using ISO/JIS-SCID N2 on Canon Photo Paper Plus Glossy II media

Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734, excluding time to print the first set.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host computer.

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100[®] please visit www.canon-europe.com/chromalife100

¹ Ink droplets can be placed with a minimum pitch of 1/4800 inch

² Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.

³ Printing Canon standard photos continuously on 10x15cm Photo Paper Plus Glossy II with default settings using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.

⁴ When printing ISO/JIS-SCID N2 pattern on A4 size Plain Paper using default settings.