

9022/9022N Mono Laser Printer

Petite and perfectly proportioned



- Up to 22 page per minute (letter)
- Choice of models for network or PC direct
- Small and compact design
- 1200 x 1200 print quality
- 10 Seconds first time to print
- Professional individuals or small workgroups



It's small but very fast

At only 278 mm high the 9022 is ideally suited for front office applications where it may have to sit under the desk and at 10 seconds first time to print the 9022 will have the job finished before many printers have even started.

Upgrade to suit your needs

Standard configuration offers two input paths; a 250 sheet cassette together with a 50 sheet multi-purpose feeder ideal for those non standard paper sizes. An additional 250 sheet cassette can be simply installed together with other performance enhancing options including PostScript 3, Memory and a LAN interface (standard on 9022N)

Plug and Go

USB2 and Parallel are standard on all models and Ethernet 10/100BaseT is standard on the 9022N giving easy connection and the ability to share resources in the small office or even home office.

Available Configuration:

9022 Standard Product

9022N with Network Interface

Print Speed	22 pages per minute; 20 ppm A4
Print Method	Laser
Processor	SPGPm 166 MHz
Resolution	1200 x 1200 dpi
Time To 1st Page	Less than 10 seconds (warm-up time less than 40 seconds)
Memory	16 MB std / max 144 MB
Standard Connectivity	Parallel (Bi-directional IEEE 1284 complaint ECP/Nibble/Byte Mode), USB (v2.0); 9022N Includes Ethernet
Optional Connectivity	Internal Ethernet (10Base-T & 100BaseT)
Standard Emulation	PCL5e/PCL6/IBM Proprinter/Epson
Optional Emulation	PostScript Level 3 PDL (Barcode TBA)
Fonts	1 Bit Map and 45 scaleable (35 intellifont, 10 TrueType), 136 PS3 fonts
Consumables	Replacement process unit: < 3,500-5,000 pages (ISO/IEC 19752)
STD Paper Handling	Manual feed, 50-sheet multi-purpose tray (MPT) + 250-sheet universal cassette
Opt'l Paper Handling	2nd universal cassette accepts 250 sheets
Duplexing	Manual
Paper Type	Paper, transparencies, labels, heavy paper stock, envelopes (Monarch, No.9, No.10, C5, DL)
Paper Weight	Cassette:60-90gsm; MPF:60-163gsm
Paper Size	Cassette: A4, letter A5, Legal, Folio, Officio, Executive, ISO B5, JIS B5, 3"x5"; MPF: All plus A6
Paper Output	150-sheet face down, 1 sheet face up
Printable Area	Paper: non printer area 3mm from each side; Envelope: 15mm from left, 10mm elsewhere
Physical Weight	Less than 10kg including consumables
PhysicalSize	358(w) x 425(d) x 278 (h) mm
Power Voltage	220-240v
Power Frequency	50/60 Hz
Power Consumption	Printing: less than 400W (average), Sleep Mode: less than 15W
Compliance	Energy Star compliant, Ozone-free, Less than 0.02 parts per million (UL478)
Workload	Up to 30,000 pages per month
Drivers	Windows 9.x/NT 4.0/2000/ME/XP/Mac via Postscript PPD, LINUX
Temperature	10°C - 32°C
Humidity	10% - 80% relative humidity, non-condensing
Acoustic	Printing - 51 dB(A); Standby - 39 dB(A); Sleep Mode - Background level
Warranty	2 years (Hot Swap)
Option 1	2nd cassette (250-sheet); SIMM with PostScript 3 & PCL Barcodes, 16/32/64/128MB Memory, Barcode SIMM; Internal Ethernet (10Base-T/100Base-T)
Note	Paper is a highly variable medium, and should be tested prior to purchase. Drum and Fuser Yields will vary based on job run length, media type, size, weight, orientation, and usage patterns.



All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH

Ver. 1.0
Printed Date: 03/07/2009

DASCOM

DASCOM GB Limited,
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400
www.dascom.com