

T2280+

High speed, rugged design for heavy duty operation



Tally

The T2265+ and T2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

- **Print speeds up to 1000 cps**
- **Full range of automatic features minimising operator intervention**
- **Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms**
- **Straight through paper path for easy forms loading**
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS**
- **Straight through paper path for easy forms loading**
- **Compatible with a wide range of operating systems including Windows, UNIX, DOS, SAP R3 and legacy systems**

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ and T2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

- T2280+
- T2280+ 2T with two additional tractors
- T2280+ IGP with IGP/PJL Support
- LA800+ DEC compatible version

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

T2280+





Print Speed	Draft: 800cps; NLQ: 222cps; LQ: 111cps
Printhead Life	500 million characters
Throughput	(ECMA 132 @ 10dpi) Letter Performance:626 pages per hour; Spreadsheet:389 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Memory	128Kb
Standard Connectivity	Bi-directional parallel plus Ethernet 10/100BaseT with 128Kb buffer
Optional Connectivity	Serial RS232, adapters, Ethernet IPDS: USB parallel adapter IBM proprinter
Standard Emulation	MTPL + barcode/LCP, Epson LQ (Esc P/2), IBM ProPrinter XL24e IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulation	MT50, MT460, Digital/Compaq model (LA800) contextual Arabic
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 Barcodes and scaleable LCP Font. Range of Arabic fonts (Arabic mode)
Consumables	Ribbon: 20 million characters
STD Paper Handling	Push tractors with paper parking and AGA; 2nd rear push tractor - 2280-2T only, 1+1 copies; Cut sheet front insertion with AGA
Optional Paper Handling	2nd front tractor (user installable); Dual bin automatic sheet feeder*, 190 sheets per bin; Face down output bin*; Paper cutting device, paper pedestal; Front feed sheet feeder, 190 sheets capacity
Paper Type	Continuous forms, cut sheets
Paper Weight	Continuous forms: 60-120gsm; Cut sheet: 60-90gsm
Paper Size	Cut sheet: 100 to 420mm wide
Physical Weight	Approximately 19Kg
Physical Size	(HxWxD): 277x623x430mm
Power Voltage	230V
Power Consumption	75W printing
Workload	50,000 pages per month
Number of Copies	Up to 6 part forms. (1+1 for rear tractors of 2280-2T)
Drivers	Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	57dB(A)
Warranty	2 years, on-site

Note *The dual bin sheet feeder and face down output bin are unsuitable for use with the 2280-2T. Exceeding the monthly duty cycle will not void the warranty if **DASCOM** consumables and maintenance kits are used.

DASCOM GB Limited
ViewPoint, Basing View,
Basingstoke, Hampshire RG21 4RG
Tel: +44 (0) 1256 481481
Fax: +44 (0) 1256 481400

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH
Ver. 1.0
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS 
MOBILE PRINTERS 
THERMAL PRINTERS 
LINE MATRIX PRINTERS 
LASER PRINTERS 